
LEDFOG201

LEDriving F1 | – LED foglight



Areas of application

- Suitable replacement for almost all modern fog lights
- Fog light

Product benefits

- 3 year guarantee
- High-quality LED technology
- Lens resistant against gravel impact according to ASTM D256 and ISO 179
- Easy installation
- Low energy consumption

Product features

- LED fog light with integrated control
- Color temperature: up to 6,000 K
- Long lifetime: up to 5,000 h
- Certified according to ECE, SAE regulations
- Type of protection: IP67K

Product datasheet

Technical data

Electrical data

Nominal voltage	12.0 V
Nominal wattage	8 W

Photometrical data

Color temperature	6000 K
-------------------	--------

Dimensions & weight

Length	114.0 mm
Product weight	460.00 g

Country specific categorizations

Order reference	LEDFOG201 BK 12
-----------------	-----------------

Product datasheet

Logistical Data

Product code	Product description	Packaging unit (Pieces/Unit)	Dimensions (length x width x height)	Volume	Gross weight
4052899197985	LEDFOG201	Folding carton box 1	286 mm x 105 mm x 204 mm	6.13 dm ³	688.00 g
4052899197992	LEDFOG201	Shipping carton box 2	310 mm x 240 mm x 245 mm	18.23 dm ³	2002.00 g

The mentioned product code describes the smallest quantity unit which can be ordered. One shipping unit can contain one or more single products. When placing an order, for the quantity please enter single or multiples of a shipping unit.

References / Links

Guarantee terms are available at

▶ www.osram.com/am-guarantee

Legal advice

ECE R19 F3 approval

Disclaimer

Subject to change without notice. Errors and omission excepted. Always make sure to use the most recent release.